



6.390 Intro to Machine Learning

Lecture 8: Representation Learning

Shen Shen

Oct 23, 2025


11am, Room 10-250


Interactive Slides and Lecture Recording

Outline


- Neural networks are representation learners
- Auto-encoders
- Word embeddings
- (Some recent representation learning ideas)

Recap: neuron







asymptotically, can approximate any function!




[images credit: visionbook.mit.edu]

Two different ways to visualize a function e.g. the identity function






Representation transformations for a variety of neural net operations



[images credit: visionbook.mit.edu]

and stack of neural net operations



Parameters


wiring graph

equation


mapping 1D


mapping 2D



















 $x_{\mathtt{out}_i} = \max(x_{\mathtt{in}_i}, 0)$






[images credit: visionbook.mit.edu]

What does training a neural net classifier look like?





$$z_2 = ext{ linear } (a_1) \in \mathbb{R}^2$$

$$a_1 = \operatorname{ReLU}(z_1)$$

 $z_1 = ext{ linear } (x) \in \mathbb{R}^2$


 z_2


 a_1

 z_1

 $x\in \mathbb{R}^2$


Training data





maps from complex data space to desired target space

[images credit: visionbook.mit.edu]





Deep neural nets transform datapoints, layer by layer

Each layer is a different representation, aka embedding, of the data

From data to latent embeddings: representation learning

(From latent embeddings to data: generative modeling)





Training

Testing

Genre recognition

Preference prediction



Often, what we will be "tested" on is not what we were trained on.

Training

Adapting

Genre recognition

Preference prediction



"common"-sense task-specific representation prediction

Final-layer adaptation: freeze f, train a new final layer to new target data

Training

Adapting

Genre recognition

Preference prediction




"common"-sense task-specific representation prediction

Finetuning: initialize f' as f, then continue training for f' as well, on new target data


Pretraining

Genre recognition




Adapting

Preference prediction



Testing

Preference prediction



A lot of data

A little data

ImageNet also taught us that labeling 14 million images by hand is brutal.


Undergrads were time-consuming, algorithms were flawed, and the team didn't have money—Li said the project failed to win any of the federal grants she applied for, receiving comments on proposals that it was shameful Princeton would research this topic, and that the only strength of proposal was that Li was a woman.

A solution finally surfaced in a chance hallway conversation with a graduate student who asked Li whether she had heard of Amazon Mechanical Turk, a service where hordes of humans sitting at computers around the world would complete small online tasks for pennies.

"He showed me the website, and I can tell you literally that day I knew the ImageNet project was going to happen," she said. "Suddenly we found a tool that could scale, that we could not possibly dream of by hiring Princeton undergrads."

Label prediction (supervised learning)

are abundant



Can we learn useful things with just x?


expensive...

Outline


- Neural networks are representation learners
- Auto-encoders
- Word embeddings
- (Some recent representation learning ideas)

Observed image

Drawn from memory




[Bartlett, 1932] [Intraub & Richardson, 1989]



[https://www.behance.net/gallery/35437979/Velocipedia]

humans also learn representations




Good representations are:


Auto-encoders explicitly aims

these may just emerge as well

- Compact (minimal)
- Explanatory (roughly sufficient
- Disentangled (independent factors)
- Interpretable (understandable by humans)
- Make subsequent problem solving easy




Auto-encoder




"What I cannot create, I do not understand." Feynman

Auto-encoder


$$\min_W ||x - ilde{x}||^2$$





[Typically, encoders can serve as a translator to get "good representations", whereas decoders can serve as "generative models"]


But it's easy to "cheat" with auto-encoders



[Vincent et al, Extracting and composing robust features with denoising autoencoders, ICML 08]


[Steck 20, Zhang et al 17]

Unsupervised Learning (feature reconstruction)




Features

Self-supervised Learning (partial feature reconstruction)




Harder reconstruction, forces understanding.



[He, et al. Masked Autoencoders Are Scalable Vision Learners, 2021]

Large Language Models (LLMs) are trained in this self-supervised way



- Scrape the internet for plain texts.
- Cook up "labels" (prediction targets) from these texts.
- Convert "unsupervised" problem into "supervised" setup.

"To date, the cleverest thinker of all time was Issac."



feature
:
To date, the
To date, the cleverest


To date, the cleverest thinker


To date, the cleverest thinker
:
To date, the cleverest thinker
:
It date, the cleverest thinker

To date, the ____ model →

Outline


- Neural networks are representation learners
- Auto-encoders
- Word embeddings
- (Some recent representation learning ideas)






Good word embeddings space is equipped with sensible dot-product similarity

For now, let's look at how good embeddings enable "soft" dictionary look-up:



```
dict_en2fr = {
   "apple": "pomme",
   "banana": "banane",
   "lemon": "citron"}


query = "lemon"
output = dict_en2fr[query]
```



What if we run

```
dict_en2fr = {
   "apple" : "pomme",
   "banana": "banane",
   "lemon" : "citron"}

query = "orange"
  output = dict_en2fr[query]
```





What if we run

```
dict_en2fr = {
   "apple" : "pomme",
   "banana": "banane",
   "lemon" : "citron"}

query = "orange"
  output = dict_en2fr[query]
```

But we can probably see the rationale behind this:






We put (query, key, value) in "good" embeddings in our human brain


such that "merging" the values 0.1 pomme + 0.1 banane + 0.8 citron


via these merging percentages [0.1 0.1 0.8] made sense

very roughly, the attention mechanism in transformers automates this process.



1. compare query and key for merging percentages:





1. compare query and key for merging percentages:

softmax
$$\left(\begin{array}{c|c} \text{orange} & \text{orange} \\ \hline \end{array}\right)$$
, $\left[\begin{array}{c|c} \text{orange} \\ \end{array}\right]$

2. then output merged values 0.1 pomme + 0.1 banane + 0.8 citron

many more bells and whistles, we'll discuss next week

Outline


- Neural networks are *representation* learners
- Auto-encoders
- Word embeddings
- (Some recent representation learning ideas)
 - 1. masking: reconstruction
 - 2. contrastive: similarity
 - 3. multi-modality: alignment

e.g. masking channels





predict color from gray-scale
















[Baade+, '22; Chong+, '22; Niizumi, '22; Huang+, '22]




e.g. robotics





Multi-View Masked Autoencoders

Visual Robotic Manipulation




[Xiao+, '22; Radosavovic+, '22; Seo+, '22;]






[Feichtenhofer, et al., "Masked Autoencoders As Spatiotemporal Learners", NeurIPS 2022]

masking 75% is optimal for images




Similar empirical studies shows 15% as optimal for languages, and 95% for videos


95% masked





98% masked



















Figure 1. ImageNet top-1 accuracy of linear classifiers trained on representations learned with different self-supervised methods (pretrained on ImageNet). Our method, SimCLR, is shown in bold.


3. Multi-modality



e.g. video, audio, images



What did the model learn?






[Owens et al, Ambient Sound Provides Supervision for Visual Learning, ECCV 2016]

e.g. image classification (done in the contrastive way)

1. Contrastive pre-training




```
# extract feature representations of each modality
I_f = image_encoder(I) #[n, d_i]
T_f = text_encoder(T) #[n, d_t]

# joint multimodal embedding [n, d_e]
I_e = 12_normalize(np.dot(I_f, W_i), axis=1)
T_e = 12_normalize(np.dot(T_f, W_t), axis=1)

# scaled pairwise cosine similarities [n, n]
logits = np.dot(I_e, T_e.T) * np.exp(t)

# symmetric loss function
labels = np.arange(n)
loss_i = cross_entropy_loss(logits, labels, axis=0)
loss_t = cross_entropy_loss(logits, labels, axis=1)
loss = (loss_i + loss_t)/2
```

e.g. image classification (done in the contrastive way)



e.g Dall-E: text-image generation




Figure 2: A high-level overview of unCLIP. Above the dotted line, we depict the CLIP training process, through which we learn a joint representation space for text and images. Below the dotted line, we depict our text-to-image generation process: a CLIP text embedding is first fed to an autoregressive or diffusion prior to produce an image embedding, and then this embedding is used to condition a diffusion decoder which produces a final image. Note that the CLIP model is frozen during training of the prior and decoder.

How Much Information is the Machine Given during Learning?

- "Pure" Reinforcement Learning (cherry)
 - The machine predicts a scalar reward given once in a while.
 - ► A few bits for some samples
- Supervised Learning (icing)
- The machine predicts a category or a few numbers for each input
- Predicting human-supplied data
- $ightharpoonup 10 \rightarrow 10,000$ bits per sample
- Self-Supervised Learning (cake génoise)
- The machine predicts any part of its input for any observed part.
- Predicts future frames in videos
- Millions of bits per sample © 2019 IEEE International Solid-State Circuits Conference



67

Summary

- We looked at the mechanics of NN. Today we see they learn representations, just like our brains do.
- This is useful because representations transfer they act as prior knowledge that enables quick learning on new tasks.
- Representations can also be learned without labels, e.g. as we do in unsupervised, or self-supervised learning. This is great since labels are expensive and limiting.
- Without labels there are many ways to learn representations:
 - representations as compressed codes, auto-encoder with bottleneck
 - (representations that are predictive of their context)
 - (representations that are shared across sensory modalities)

We'd love to hear

your thoughts.
Thanks!