


Name: \_\_\_\_\_

## Nearest neighbor classifiers

4. (12 points) This question asks about learning nearest neighbor (NN) classifiers. Assume that we are using Euclidean distance squared as the distance metric, i.e.  $d(x, x') = \|x - x'\|^2$ .

(a) Draw on the below figure the decision boundary for a 1-NN classifier on this data set. In each region, denote whether the classification of any point (*any* point, not just the training data) in that region would be +1 or -1. (Note, all data points are assumed to be on integer coordinates.)



- (b) Which training data points, if any, could you remove and keep the decision boundary identical? Answer using their  $(x_1, x_2)$  coordinates.

- (c) You perform leave-one-out cross-validation of the 1-NN and 3-NN classifiers on this data set, i.e. you use cross-validation with a chunk size of 1 data point. Assume ties go to the +1 region. What cross-validation errors do you obtain?

1-NN:

3-NN:

Name: \_\_\_\_\_


- (d) Suppose we now use the following feature transformation,  $\phi(x_1, x_2) = x_1x_2$ , and seek to learn a nearest neighbor classifier in the transformed space. This is equivalent to using a different distance metric,  $d(x, x') = \|\phi(x) - \phi(x')\|^2$ . What is the average leave-one-out cross-validation error of a 3-NN classifier using this new distance metric? Which points would be misclassified (specified using their  $(x_1, x_2)$  coordinates)?

3-NN:


Misclassified points:

- (e) The plots below show the decision boundaries as predicted by a k-NN classifier for four different values of  $k$ : 1, 5, 20, 40. Map each plot to the corresponding value of  $k$ .


(I)




(II)



(III)



(IV)



$k = 1$ :	<input type="radio"/> (I)	<input type="radio"/> (II)	<input type="radio"/> (III)	<input type="radio"/> (IV)
$k = 5$ :	<input type="radio"/> (I)	<input type="radio"/> (II)	<input type="radio"/> (III)	<input type="radio"/> (IV)
$k = 20$ :	<input type="radio"/> (I)	<input type="radio"/> (II)	<input type="radio"/> (III)	<input type="radio"/> (IV)
$k = 40$ :	<input type="radio"/> (I)	<input type="radio"/> (II)	<input type="radio"/> (III)	<input type="radio"/> (IV)